

KRK CLASSIC SERIES

Building on KRK's legacy of sonic accuracy and performance, the new KRK CLASSIC series of powered studio monitors incorporate over 30 years of innovation from the world's leading studio monitor manufacturer. Borrowing concepts from previous ROKIT lines—some of the most used studio monitors in the world, the CLASSIC series defaults to a new flat frequency solution towards more critical listening—translating into more accurate mixes. With the optional ability to engage the +2 dB KRK Bass Boost, the CLASSIC series can also provide the enhanced bass response and sound that music creators around the world have loved for years.

The CLASSIC series are active (self-powered) two-way studio monitors that utilize a 1" textile soft dome tweeter paired with a 5", 7", or 8" (depending on the specific model) glass aramid woofer. The built-in bi-amped power amplifiers provide a total of 50, 73, or 100 watts of power (again, depending on the model), and all models in the series deliver natural and balanced spectral response with low distortion and superior stereo imaging. With KRK studio monitors, you'll hear every nuance of the audio being reproduced.



CLASSIC 5**CLASSIC 7****CLASSIC 8**

CONFIGURATION	2-WAY		
SYSTEM TYPE	ACTIVE MONITOR		
TRANSDUCERS	5" GLASS ARAMID WOOFER, 1" TEXTILE SOFT DOME TWEETER	7" GLASS ARAMID WOOFER, 1" TEXTILE SOFT DOME TWEETER	8" GLASS ARAMID FIBER WOOFER, 1" TEXTILE SOFT DOME TWEETER
FREQUENCY RESPONSE (+/- 3dB)	56 Hz - 30 kHz	47.5 Hz - 34.5 kHz	42.5 Hz - 28 kHz
FREQUENCY RANGE (-10dB)	46 Hz - 34.5 kHz	37 Hz - 40 kHz	35 Hz - 35 kHz
MAX PEAK SPL	101 dB SPL		106 dB SPL
AMPLIFIER POWER RATING	HIGH FREQUENCY: 20 W LOW FREQUENCY: 30 W	HIGH FREQUENCY: 25 W LOW FREQUENCY: 48 W	HIGH FREQUENCY: 25 W LOW FREQUENCY: 75 W
INPUT IMPEDANCE	10 K Ω BALANCED / 7 K Ω UNBALANCED		
CONNECTORS	INPUT: RCA, BALANCED 1/4" TRS, BALANCED XLR		
CONTROLS	SYSTEM VOLUME -30 DB - +6 DB		
LF/HF LEVEL ADJUST	LF: (-1 dB, FLAT, +1 dB, +2 dB) BELOW 200 HZ HF: (-2 dB, FLAT, -1 dB, +1 dB) ABOVE 2.6 KHZ	LF: (-2 dB, -1 dB, FLAT, +2 dB) BELOW 200 HZ HF: (-2 dB, -1 dB, FLAT, +1 dB) ABOVE 2.3 KHZ	LF: (-2 dB, -1 dB, FLAT, +2 dB) BELOW 200 HZ HF: (-2 dB, -1 dB, FLAT, +1 dB) ABOVE 2.0 KHZ
ENCLOSURE CONSTRUCTION	15 mm MDF / HIGH IMPACT POLYSTYRENE		
FINISH	BLACK VINYL WRAP		
HARDWARE	FOAM ISOLATION PAD		
DIMENSIONS (H X W X D)	9.68" (246 mm) x 7.40" (188 mm) x 11.20" (283 mm)	11.40" (290 mm) x 8.90" (226 mm) x 13.07" (332 mm)	12.40" (315 mm) x 10.82" (275 mm) x 15.60" (396 mm)
WEIGHT	12.95 lb (5.87 kg)	18.5 lb (8.39 kg)	24.6 lb (11.16 kg)