

ALPHA 65 EVO

Product sheet

Alpha 65 Evo has a 1" (25mm) Aluminium tweeter and a 6.5" (16.5cm) woofer with Slatefiber cone developed and manufactured in Focal's workshops in France. This monitor features excellent dynamics and neutrality in its tonal balance. Thanks to new technologies and features, Alpha 65 Evo is highly versatile.



Key points

- Excellent dynamics
- Wide dispersion enabling the same sound to be maintained throughout the entire room
- Slatefiber cone manufactured in France: sound neutrality, no distortion
- Identical tonal balance at both low and high volume
- Connect up to 3 audio sources
- Inserts for wall fastening
- Protective grills included

Type	Alpha 65 Evo Monitoring		
Frequency response (+/- 3dB)	40Hz - 22kHz	Level midrange/bass (0 - 300Hz)	Adjustable, +/-6dB
Maximum SPL	104dB SPL (peak @39 ³ / ₈ " (1m))	Treble level (4.5 - 22kHz)	Adjustable, +/-3dB
Inputs Connectors	TRS: symmetrical 10kOhms XLR: symmetrical 10kOhms RCA: asymmetrical 10kOhms with compensated sensitivity	Power on/off	On/off switch on the rear panel
Medium and low frequency amplifier	55W (music), class D	Stand-by consumption	<0.5W
High frequency amplifier	25W (music), class D	Views and controls	On and off LED - Stand-by LED
Automatic stand-by mode	After around 15 minutes of no use By signal detection >6mV	Woofers	6.5" (16.5cm) Slatefiber cone
Power supply	100 - 240V- (T2AL fuse/250V)	Tweeters	25mm (1") with aluminium inverted dome
Connection	IEC socket and detachable power cable	Construction	0.6" (15mm) MDF
Sensitivity	Adjustable, 0 or +6dB	Finish	Black vinyl and paint
		Dimensions with 4 rubber feet (HxWxD)	13.35 x 10.28 x 11.38" (339 x 261 x 289mm)
		Weight	16.8lbs (7.6kg)